	Technical data sheet	GS-002-01 /-002-05
	<h1>Remover G-PLUS</h1>	Issue date: 17.01.2014
		Valid until:
		Version: 1.1

1. Product information

Remover G-PLUS is an alkaline graffiti- & bitumen-remover for persistent graffiti and color shadows on untreated or treated surfaces with Perma-Guard [Article GE-009-01 / -009-05 up to 012-01 / -012-05].

2. Application

Remover G-PLUS removes persistent graffiti-, bitumen- and color shadows on porous and non-porous surfaces; e.g. clinker brick, ceramic, natural stone, brick work, concrete, various metals and plastics. Remover G-PLUS can also be used on surfaces which have already been treated with Perma-Guard for the removal of color shadows.

Attention: Dispersion and lacquer colors can quickly be dissolved!

Before the application on primed or lacquered surfaces, always check the compatibility.

3. Characteristics

- Easy application
- Removal of persistent color shadows made by color spray and permanent marker colors
- Suitable for many different surfaces
- Easy and fast cleaning of color shadows on surfaces treated with Anti-Graffiti-coating [Perma-Guard]!

4. Technical data

Color :	brown
Density :	approx. 1.03 g/cm ³
Application rate :	The consumption depends on the porosity of the surface as well as the type and age of the graffiti. Approx. 0,20 - 0,33 l/m ² .
Dilution :	Do not thin
Flashpoint :	>41°C

5. Application data

Application areas: Useable outside and inside [in well vented rooms].

The surface has to be dry prior to the application. Wear safety gloves! Remover G-PLUS must not be applied with an atomiser [chemical burn of the respiratory tract].

ATTENTION! Before starting a cleaning procedure, always check the compatibility of the surface with the graffiti remover on a test area.

Surfaces without Anti-Graffiti-coating

Apply Remover G-PLUS by brush, paint brush or sponge [wear protective gloves].

Leave on Remover G-PLUS for approx. 5 minutes depending on the surface compatibility. Work on small areas at a time. Do not apply Remover G-PLUS on too big of surfaces and keep checking the dissolution progress. Remove the graffiti with warm water, preferably with a high pressure cleaner at low pressure and flat spray nozzle. Small surfaces can be rinsed thoroughly with warm water and wiped down with clean cloth.

Surfaces with Anti-Graffiti-coating

Apply Remover G-PLUS with soft brush, soft paint brush or sponge with white pad [wear protective gloves]. Leave on Remover G-PLUS for approx. 5 minutes. Work on small areas at a time. Do not apply Remover G-

Vertrieb Deutschland

GUARD KG


Berta-Cramer-Ring 26

D-65205 Wiesbaden

Tel: +49 (0)6122 / 704 63 16

Email: info@graffiti-guard.net

www.graffiti-guard.net

	Technical data sheet Remover G-PLUS	GS-002-01 /-002-05
		Issue date: 17.01.2014
		Valid until:
		Version: 1.1

PLUS on too big of surfaces. Remove the graffiti with warm water, brush and/or soft cloth. **Do not use a high pressure device!! Finally, neutralize the treated surface with enough water!!**
 Further treatments may be required for persistent permanent marker colors or old graffiti.

Note – Color shadows after graffiti removal / color shadows removal

With old Graffiti it may be required to leave on the Remover G-PLUS for longer periods of time. Repeat the cleaning process multiple times on dry surface.

Should there be left over shadows of graffiti on uncoated surfaces (e.g. permanent marker colors), the following products could be used depending on the surface: Shadow G (Article GS-005-01 /-005-05 /-005-10) or Bleach G (Article GE-006-01 /-006-05) On coated surfaces light color shadows can be removed with a mild bleach (drugstore) or Bleach G (Article GE-006-01 /-006-05).

6. Packaging sizes

1 l / 5 l

7. Storage

In sealed and original packing stable for a minimum of 12 months. Store containers cool and dry and protect against frost.

8. Safety data

See safety data sheet

The information and data in this technical data sheet are based on our practical experience and knowledge. Due to different practice requirements a general liability is being excluded. Own trials with regard to the suitability and application by the user are to be done. With the release of a new technical data sheet, all former versions become void.
