

	Technical data sheet <h1 style="margin: 0;">Shadow G</h1>	GS-005-01 /-005-05 /-005-10
		Issue date: 17.01.2014
		Valid until:
		Version: 1.1

1. Product information

Shadow G is a high quality, viscous and alkaline cleaner for the removal of persistent graffiti shadows on untreated or treated surfaces with Perma-Guard [Article GE-009-01 / -009-05 up to 012-01 / -012-05].

2. Application

Shadow-G removes persistent color shadows made by color sprays and permanent marker colors on non-primed and porous surfaces e.g. clinker, ceramic, natural stone, brick work, concrete and various plastics as well as metals except zinc and aluminum. Always check the compatibility of the surface with the graffiti remover on a test area.

3. Characteristics

- Easy application
- Fast and effective removal of persistent graffiti shadows
- Does not affect the surface
- Suitable for many different surfaces

4. Technical data

Color :	Yellow-brown
Density :	approx. 1.03 g/cm ³
Application rate :	The consumption depends on the porosity of the surface as well as the type and age of the graffiti. Approx. 0,20 - 0,50 l/m ²
Dilution :	Do not thin

5. Application data

Application areas: Useable outside and inside [in well vented rooms].

The surface has to be dry prior to the application. Wear safety gloves! Shadow-G must not be applied with an atomiser [chemical burn of the respiratory tract].

ATTENTION! Before starting a cleaning procedure, always check the compatibility of the surface with the graffiti remover on a test area.

Surfaces without Anti-Graffiti-coating

Apply Shadow G by brush, paint brush or sponge [wear protective gloves]. The surface has to be well saturated with Shadow-G then leave on for 10-30 minutes.

Remove the graffiti shadows with warm water, preferably with a high pressure cleaner at medium pressure and flat spray nozzle. Small surfaces can be rinsed thoroughly with warm water and wiped down with clean cloths.

Surfaces with Anti-Graffiti-coating

Apply Shadow G with soft brush, soft paint brush or sponge with white pad [wear protective gloves]. Leave on Shadow G for approx. 5 minutes. Work on small areas at a time.

Do not apply Shadow G on too big of surfaces. Remove the graffiti with warm water, brush and/or soft cloth.

Do not use a high pressure device!! Finally, neutralize the treated surface with enough water!!

Further treatments may be required for persistent permanent marker colors or old graffiti.

 Graffiti-Guard Anti-Graffiti-System	Technical data sheet	GS-005-01 /-005-05 /-005-10
	Shadow G	Issue date: 17.01.2014
		Valid until:
		Version: 1.1

Note – Light color shadows after color shadows removal

With old graffiti it may be required to leave on Shadow-G for longer periods of time.

Repeat the cleaning process multiple times on dry surface.

Should there be left over shadows of graffiti (e.g. permanent marker colors), light color shadows can be removed with NACLO 13 or Bleach G (Article GE-006-01 /-006-05).

6. Packaging sizes

1 L / 5 L / 10 L

7. Storage

In sealed and original packing stable for a minimum of 12 months. Store containers cool and dry and protect against frost.

8. Safety data

See safety data sheet

The information and data in this technical data sheet are based on our practical experience and knowledge. Due to different practice requirements a general liability is being excluded. Own trials with regard to the suitability and application by the user are to be done. With the release of a new technical data sheet, all former versions become void.
